

T10L



Specifications

Processor	Intel N450 CPU, 1.66 GHz
Chipset	South Bridge: ICH8-M
System Memory	One 200-pins DDRII 667 SO-DIMM Socket for 2GB RAM Module
Mass Storage	1.8" SATA 4200RPM HDD 120GB 1.8" SATA SSD 32 GB (Optional)
Audio	Build in 2W speaker Build in Stereo Microphone Array
Display	10.4" XGA (1024x768) TFT LCD with touch screen panel Luminance:240 nit LED Backlight Use Hotkey (Fn+2) to switch Landscape/Portrait mode Automatically adjust the brightness of LCD as the changing background
Touch screen	4 wire resistive type Anti-glare Palm rejection implemented
I / O Ports	DC-in jack Two battery slots Docking connector(contact pin type) Smart card reader + One USB port (Optional)
I/O Devices	One 2 mega-pixel camera with auto-focus feature One Barcode scanner supports 1D/ 2D barcode One RFID reader supports ISO 14443 A/B & ISO 15693 (Intel MCA platform driver doesn't support ISO 14443A/B) One Finger print scanner
Wireless/Communications	Mini PCI Express card Wireless LAN 802.11b/g/n Support CCX function (Roaming) Bluetooth v2.1 and support Enhanced Data Rate (EDR) 3G module for WWAN (Optional)
AC / DC Adapter	I.T.E. AC power input: 100V-240V,50Hz-60Hz output: 65W,19V Medical AC power input:100V-240V,47Hz-63Hz output: 78W, 18V (optional)
Battery	Hot swappable function: Dual battery pack design Per battery pack: 3 lithium-ion high capacity cells (3S1P), 2400mAh, 2hrs 40 min
Dimension & Weight	270 x 256 x 35.3 mm 1.34 kg (2.96 lb)(with one battery pack)
Operating System	Windows 7 32Bit

Military Standard Toughness

Humidity & Temperature	Operating Humidity : 10% ~ 90% Operating Environment Temperature : 0°C ~50°C Storage Environment Temperature : -20°C ~60°C
Drop Specification	3 feet height of free drop
Water Sealing	IP 65 The device enclosure can resist alcohol (80% or less), bleach, iodine and common hospital disinfectants.



Taipei (Headquarters)
Twinhead International Corporation
10F,550, Rueiguang Road,
Neihu,Taipei, 114,Taiwan, R.O.C.
Tel : 886-2-5589-9999
Fax: 886-2-5555-7777
<http://www.twinhead.com>

U.S.A.
GammaTech Computer Corp.
48303 Fremont Blvd.
Fremont, CA94538, U.S.A.
Tel : 1-510-492-0828
Fax: 1-510-492-0820

Germany
Twinhead GmbH
Nikolaus-Otto-Strasse 4
40670 Meerbusch-Osterath Germany
Tel : +49 (0)2159-6944-0
Fax: +49 (0)2159-6944-20
<http://www.twinhead.de>

